




# Heat pump integration and application in nearly Zero Energy Buildings (nZEB)

BFE IEA Networking Event Switzerland,  
May 24, 2022, Eventforum, Berne

## Motivation

- **Nearly Zero Energy Buildings (nZEB) are the global future building standard**
- **In the USA and Canada as well as in China and Japan nZEB will be introduced between 2020 - 2030**
- **Since Jan 1, 2021, all new buildings in the EU have to comply with nZEB requirements**
  - Despite different harmonisation initiatives, different national implementations in the member states leading to different ambition levels
  - In Switzerland implemented by MuKEn 2014
- **Building technology to reach nZEB is of particular interest**
  - Heat pumps are already well established as building technology for nZEB
  - nZEB can become a market driver for heat pumps



# Heat pump integration/application for nZEB - HPT Annex 49

## Research in IEA HPT Annex 49

- 8 participating countries, 16 institutions


 AT BE CH DE NO SE UK US

- State of the art of nZEB in participating countries

- Definition and ambition level of nZEB

- Integration of multi-functional heat pumps in nZEB


- Integration with storages, solar components and the ground

- Monitoring of marketable/prototype heat pumps in nZEB




- Focus on larger residential and non-residential nZEB with heat pump

- Design and control of heat pump systems for nZEB

- Increase of self-consumption and energy flexibility




source: JRC




## State of nZEB implementation

- **Methodology to compare nZEB ambition level**
  - Elaborated by AT, CH and DE
  - Method based on building and system simulation
  - Test for a single family house (based on Reference framework of IEA HPT Annex 38/SHC Task 44)
  - Implementation of building based on national nZEB rating and transformation to common boundary conditions
  - Relative comparison of ambition levels possible
  - Current limitations
    - limited countries tested (AT, CH, DE, IT, SE)
    - Single family building use
    - A-W heat pump heating and DHW system




source:  
IEA SHC Task 44/  
IEA HPT Annex 38



## State of nZEB implementation

- Results for monthly electric energy consumption with air-to-water HP
- Comparison to a passive house in the same location and same boundary conditions (DHW demand, internal loads etc.)
- In IT Rome, cooling demand in summer




## State of nZEB implementation

- Results for net electric energy consumption**

- IT and CH set additional requirements for on-site renewable energy production

Country/ regulation	Energies [kWh/m <sup>2</sup> /yr]	National nZEB	On-site PV yield	Net balance
AT OIB 6 Innsbruck		26.0	0	26.0
CH MuKEn Zurich		18.3	14.9	3.4
DE EnEV Potsdam		42.0	0	42.0
DE KfW55 Potsdam		26.1	0	26.1
SE BBR Stockholm		26.7	0	26.7
IT DM 2015 Bolzano		15.8	18.8	-3.0
IT DM 2015 Rome		16.3	17.0	-0.7



## State of nZEB implementation - Conclusions


- **Methodology to compare nZEB ambition level**
  - Different nZEB implementations and ambition levels among EU member states
  - EU cost optimality guideline (2012) and recommendation (2016) set reasonably ambitious nZEB targets for the new built sector
  - Some national nZEB implementations do not meet EU recommendations and cost optimal levels
  - Developed methodology enables a relative comparison based on building/system simulation to enhance transparency
  - Results can be used to further develop requirements and enhance ambition levels

Site	nZEB	EU	$\Delta$ [%]	Net	EU	$\Delta$ [%]
AT	70	57.5	122	70	22.5	311
CH	51	57.5	89	13.5	22.5	60
DE E	110	57.5	191	110	22.5	489
DE K	70	57.5	122	70	22.5	311
SE	72	77.5	93	72	52.5	137
IT B	45	60	75	-2.5	30	-108
IT R	46	57.5	80	3.2	7.5	43

Legend: DE E – DE EnEV, DE K – DE KfW55, IT B Italy Bolzano, IT R – Italy Rome,  $\Delta$  - percent deviation, nZEB – energy demand national nZEB, net – Net balance national nZEB, EU – EU recommendation benchmark


## nZEB Monitoring and Simulation

- **Single family building Berghalde, Stuttgart-Leonberg**
  - 260 m<sup>2</sup>, 4 inhabitants, Plus-energy house of initiative "Effizienzhaus Plus"
  - Building envelope on passive house level
  - 10 kW ground-coupled heat pump, 3 boreholes of 100 m each
  - Mechanical ventilation with 85% heat recovery efficiency and 80 m ground-to-air heat exchanger
  - Whole roof covered with 15.3 kW<sub>p</sub> solar PV system
  - 825 l thermal buffer storage and 7 – 27 kWh electric battery
- **6 years of Monitoring**




## nZEB Monitoring and Simulation

- **Plus energy balance could be confirmed for each year of the measurements**
  - High heat pump performance in the range of an SPF of 5
  - Additional investigations for load management options with control and storage integration



source: TU Braunschweig





## nZEB Monitoring and Simulation

- **Five storey multi-family passive house nZEB**
  - 1700 m<sup>2</sup> ERA, 10 flats, built in 2018
  - Monitoring in 2019
- **Building and system technology**
  - Building envelope on passive house level
  - 23 kW ground-source heat pump with free-cooling, 2 borehole ground probes of 200 m each
  - Mechanical ventilation with heat recovery
  - 81.3 kW<sub>p</sub> PV, 44.5 kW<sub>p</sub> on the roof and 36.8 kW<sub>p</sub> façade-integrated (SW and SE)
  - 78 kWh electric battery, shared battery electric vehicle




source: arento

## nZEB Monitoring and Simulation

### • Monitoring results 2019

- Surplus in annual PV-production of about 40%, SPF HP in the range of 4.5
- In 6 summer month about 90% autarky, during 9 month PV-surplus
- **However, occupancy of the building was rather low in 2019 (26 persons)**
- With higher occupancy, PV surplus is reduced




# Summary monitoring results of nZEB with HP

- **15 partly long-term monitorings in larger nZEB**
  - High SPF of the heat pump up to 5.5 for all building services approved
  - Ambitious nZEB targets may remain a challenge in larger buildings
- **Conclusions**
  - High performance building envelope and high heat pump performance are a prerequisite to reach ambitious nZEB targets in larger buildings
  - Large solar PV installation in the building envelope required, but building envelope may be a limitation in larger buildings
  - System integration of different building functions can further increase the heat pump performance



## Prototype developments

- **Prototype developments in Annex 49 refer to integrations of multiple functions in one packaged unit, e.g.**
- **Prototype development of façade integrated heat pump**
  - PV installed in the façade
  - Heat pump integrated behind PV panel
  - Cooling operation of adjacent office room shall enable an autarkic cooling operation driven by the PV modules
- **Integrated façade module**
  - Heat pump with connection to water circuit (cooling ceiling, TABS) and air cooling by fan coil
  - Integrated electric battery
- **Investigation of prototypes**
  - Simulations of prototypes for different boundary conditions (e.g. Façade, location, grid coupled, climate)
  - Monitoring in Test cells on the Campus of TU Graz



## Prototype developments

### • Simulations results

- At site Graz the typical cooling demand of an office room can be almost entirely covered by PV
- In heating operation about 60% of the demand can be covered

### • Monitoring results

- Both heating and cooling operation could be successfully operated in the test cells
- Cooled cells are about 3-6 K colder than an uncooled room
- Max. temperatures of 27 °C could be kept

### • Development

- Integration of an electric battery is to question
- Facade integration of multiple modules will be analysed



## IEA HPT Annex 49 - Conclusions


- **State of nZEB**
  - Different nZEB implementations and ambition levels which are hard to compare
  - Developed methodology enables relative comparison and transparency of implementation
  - More harmonised implementation enables more standardised HP system solutions
- **Results IEA HPT Annex 49**
  - High performance of the investigated heat pumps in nZEB application in larger buildings
  - Integration of different buildings services increases heat pump performance and cost-efficiency
  - In larger buildings reaching the nZEB balance can be a challenge despite high HP performance
  - In turn ambitious nZEB requirements can become a market driver for heat pumps
- **Integration of nZEB**
  - Integration of groups of buildings can further increase load balancing and flexibility
  - Demand response has higher importance in nZEB as active component in future energy grids



# Heat pump integration/application for nZEB - HPT Annex 49

## Results of IEA HPT Annex 49

- **Results of IEA HPT Annex 49 are documented in the following final documents**
  - Executive summary (2 page and 7 page)
  - Final report and parts
    - Part 1: State-of-the-art of heat pumps in nZEB
    - Part 2: Monitoring in nZEB with heat pumps
    - Part 3: Integration/Design/Control for heat pumps in nZEB
    - Part 4: Prototype developments of integrated heat pumps
    - 4-page Best practice sheets of monitored systems
- **For download of IEA HPT Annex 49 deliverables please visit <https://heatpumpingtechnologies.org/annex49/deliverables>**



# New Annex on Heat Pumps in positive energy districts

- New upcoming Annex for Heat pump in Positive energy districts (PED) with the topics
- State of heat pumps in positive energy neighbourhoods
- Techno-economic concept analysis by modelling and simulation of HP system integration, design and control
  - For clusters of buildings and neighbourhoods
  - For new built and retrofit
- Accompanying field monitoring of heat pumps in cluster of buildings and neighbourhoods
- State: Online Kick-off meeting, next meeting in presence planned for July, 4-5, Univ. of Innsbruck



# IEA HPT Annex 58: High-Temperature Heat Pumps (HTHP)

08 Feb 2022: **Switzerland has joined Annex 58**



- **Operating Agent:** Benjamin Zühlsdorf, PhD, [bez@dti.dk](mailto:bez@dti.dk), Danish Technological Institute
- **Participating Countries:** Austria, Belgium, Canada, Denmark, France, Germany, Japan, Netherlands, Norway, **Switzerland**
- **Duration:** 01/2021 to 12/2023
- **Homepage:** <https://heatpumpingtechnologies.org/annex58>
- **Objectives:** Overview of HTHP technologies, potentials, perspectives, concepts and strategies for process heat with supply temperatures above 100 °C
- **Overview of Activities:**


## Project Partners



Dr. Cordin Arpagaus

[cordin.arpagaus@ost.ch](mailto:cordin.arpagaus@ost.ch)

**Industrial Partners**  
supporting with Case Studies



**Thank you for your attention**

